

## RIBBON LED

series: RIBBON



Led lights



Direct



IP 20



Surface mounted

### 1485 × 67 × 62 mm

Suspended or surface mounted LED modular system designed for indoor use  
Self-supporting LED holding track made of white powder coated steel sheet (RAL 9003)

Lighting track made of white powder coated steel sheet (RAL 9003)

LED optics - 60°, 90°, 25°(both-sides asymmetrical), 30° and 84-35° are optional according to order number

Optics 84-35° is especially suitable for illumination of corridors

Mounting without tools

Luminaire equipped with electronic or dimmable electronic ballast

Continuous wiring from 3 × 1,5 mm<sup>2</sup> to 9 × 2,5 mm<sup>2</sup>

Usage: industry, warehouses, rack warehouses, high halls, low halls, garages, sport places, fuel stations

Accessories to be ordered separately

### Product description

Product code

**0-225101.000**

Driver

**EVG**

Optics

**60° LED optics**

Colour

**white**

Dimension a

**1485 mm**

Dimension b

**67 mm**

Dimension c

**62 mm**

Type of light source

**LED**

Total power consumption

**53 W**

Luminous flux

**7295 lm**

Color temperature

**3000 K**

Color index (RA)

**80**

Mounting type

**surface mounted, suspended**

Cover

**IP 20**

Weight

**2.4 kg**



### Photometry

RIBBON LED - 1485 x 67 x 62 mm

