





RIBBON LED

series: RIBBON

-  Led lights
-  Direct
-  IP 20
-  Surface mounted

1485 × 67 × 62 mm

Suspended or surface mounted LED modular system designed for indoor use
Self-supporting LED holding track made of white powder coated steel sheet (RAL 9003)

Lighting track made of white powder coated steel sheet (RAL 9003)

LED optics - 60°, 90°, 25°(both-sides asymmetrical), 30° and 84-35° are optional according to order number

Optics 84-35° is especially suitable for illumination of corridors

Mounting without tools

Luminaire equipped with electronic or dimmable electronic ballast

Continuous wiring from 3 × 1,5 mm² to 9 × 2,5 mm²

Usage: industry, warehouses, rack warehouses, high halls, low halls, garages, sport places, fuel stations

Accessories to be ordered separately

Product description

Product code

0-225102.000

Driver

EVG

Optics

60° LED optics

Colour

white

Dimension a

1485 mm

Dimension b

67 mm

Dimension c

62 mm

Type of light source

LED

Total power consumption

53 W

Luminous flux

7640 lm

Color temperature

4000 K

Color index (RA)

80

Mounting type

surface mounted, suspended

Cover

IP 20

Weight

2.4 kg



Photometry

RIBBON LED - 1485 x 67 x 62 mm

