





RIBBON LED

series: RIBBON

-  Led lights
-  Direct
-  IP 20
-  Surface mounted

1485 × 67 × 62 mm

Suspended or surface mounted LED modular system designed for indoor use
Self-supporting LED holding track made of white powder coated steel sheet (RAL 9003)

Lighting track made of white powder coated steel sheet (RAL 9003)
LED optics - 60°, 90°, 25°(both-sides asymmetrical), 30° and 84-35° are optional according to order number

Optics 84-35° is especially suitable for illumination of corridors

Mounting without tools

Luminaire equipped with electronic or dimmable electronic ballast

Continuous wiring from 3 × 1,5 mm² to 9 × 2,5 mm²

Usage: industry, warehouses, rack warehouses, high halls, low halls, garages, sport places, fuel stations

Accessories to be ordered separately

Product description

Product code
0-225104.000

Driver
EVG

Optics
60° LED optics

Colour
white

Dimension a
1485 mm

Dimension b
67 mm

Dimension c
62 mm

Type of light source
LED

Total power consumption
63 W

Luminous flux
8785 lm

Color temperature
4000 K

Color index (RA)
80

Mounting type
surface mounted, suspended

Cover
IP 20

Weight
2.4 kg



Photometry

RIBBON LED - 1485 x 67 x 62 mm

