





## RIBBON LED

series: RIBBON

-  Led lights
-  Direct
-  IP 20
-  Surface mounted

**1485 × 67 × 62 mm**

Suspended or surface mounted LED modular system designed for indoor use  
 Self-supporting LED holding track made of white powder coated steel sheet (RAL 9003)

Lighting track made of white powder coated steel sheet (RAL 9003)  
 LED optics - 60°, 90°, 25°(both-sides asymmetrical), 30° and 84-35° are optional  
 according to order number

Optics 84-35° is especially suitable for illumination of corridors

Mounting without tools

Luminaire equipped with electronic or dimmable electronic ballast

Continuous wiring from 3 × 1,5 mm<sup>2</sup> to 9 × 2,5 mm<sup>2</sup>

Usage: industry, warehouses, rack warehouses, high halls, low halls, garages, sport  
 places, fuel stations

Accessories to be ordered separately

### Product description

Product code	Driver
<b>0-225113.000</b>	<b>EVG</b>
Optics	Colour
<b>90° LED optics</b>	<b>white</b>
Dimension a	Dimension b
<b>1485 mm</b>	<b>67 mm</b>
Dimension c	Type of light source
<b>62 mm</b>	<b>LED</b>
Total power consumption	Luminous flux
<b>63 W</b>	<b>8385 lm</b>
Color temperature	Color index (RA)
<b>3000 K</b>	<b>80</b>
Mounting type	Cover
<b>surface mounted, suspended</b>	<b>IP 20</b>
Weight	
<b>2.4 kg</b>	

### Photometry

RIBBON LED - 1485 x 67 x 62 mm

